

Technical specifications

	IRFU 30	IRFU 38	IRFU 45
Diameter of the vibrator head mm	30	38	45
Length of the vibrator head mm	353	353	382
Weight of the vibrator head kg	1.4	2.2	3.5
Protective hose m	5	5	5
Operating weight kg	11.5	13.6	16
Effective diameter * cm	40	50	60
Vibrations rpm	12,000	12,000	12,000
Engine / Motor	High-frequency squirrel cage motor with integrated electronic frequency converter in the switch housing	High-frequency squirrel cage motor with integrated electronic frequency converter in the switch housing	High-frequency squirrel cage motor with integrated electronic frequency converter in the switch housing
Voltage ** 1~ V	240	240	240
Current A	2.2	3.5	4.8
Frequency Hz	50 - 60	50 - 60	50 - 60
Power cable m	15	15	15
Feed cable m	0.5	0.5	0.5

	IRFU 57	IRFU 65
Diameter of the vibrator head mm	57	65
Length of the vibrator head mm	400	490
Weight of the vibrator head kg	5.8	9.2
Protective hose m	5	5
Operating weight kg	19.8	25.5
Effective diameter * cm	85	100
Vibrations rpm	12,000	12,000
Engine / Motor	High-frequency squirrel cage motor with integrated electronic frequency converter in the switch housing	High-frequency squirrel cage motor with integrated electronic frequency converter in the switch housing
Voltage ** 1~ V	240	240
Current A	6	10
Frequency Hz	50 - 60	50 - 60
Power cable m	15	15
Feed cable m	0.5	0.5