



A	Height	2,570 mm
B	Width	1,990 mm
C	Transport length	5,499 mm
D	Digging depth max. Max. (short dipperstick)	3,501 mm
D	Digging depth max. Max. (long dipperstick)	3,751 mm
E	Insertion depth Max. vertical (short dipperstick)	2,667 mm
E	Insertion depth Max. vertical (long dipperstick)	2,906 mm
F	Insertion height Max. (short dipperstick)	5,299 mm
F	Insertion height Max. (long dipperstick)	5,459 mm
G	Dump height max. Max. (short dipperstick)	3,678 mm
G	Dump height max. Max. (long dipperstick)	3,837 mm
H	Digging radius max. Max. (short dipperstick)	5,987 mm
H	Digging radius max. Max. (long dipperstick)	6,225 mm

I	Range on the ground (short dipperstick)	5,860 mm
I	Range on the ground (long dipperstick)	6,104 mm
J	Rear swivel radius Min.	995 mm
K	Arm displacement Max. to middle of bucket right side	956 mm
K	Arm displacement Max. to middle of bucket left side	893 mm
L	Lift height Max. levelling blade above formation	415 mm
M	Scraping depth Max. of levelling blade below formation	453 mm
N	Length of running gear	2,500 mm
O	Turning angle Max. arm system to the right	61 °
P	Turning angle Max. arm system to the left	65 °
Q	Chain width	400 mm