

Neuson Fourwheel drive dumper

Technical Data

6001



Capacity

	Front tip	Swivel
Max. safe load	6000 kg	6000 kg
Unladen weight	4100 kg	4320 kg
Skip - struck	2400 kg	2400 l
- heaped	3200 kg	3200 l
- water level	1880 kg	1880 l
- swing	180-212 °	180-212 °



Engine

Make	Perkins
Type	1104C-44 with Powershuttle gearbox 4-cyl., water cooled

Output (Iso 3046/1)	61,5 (83,6) kw (hp)
Revolution	2200 min-1
Displacement	4400 ccm
Max. Torque	308 Nm
Emission	acc. 97/68/EG, step 2

Option

Make	Perkins (with powershift)
Type	1104C-44T turbo charged 4-cyl., water cooled

Output (Iso 3046/1)	74,5 (100) kw (hp)
Revolution	2200 min-1
Displacement	4400 ccm
Max. Torque	415 Nm
Emission	acc. 97/68/EG, step 2



Drive characteristics

Speed I	0 - 4,5 km/h
Speed II	0 - 7,0 km/h
Speed III	0 - 14 km/h
Speed IV	0 - 27 km/h
Steering angle	+/- 32,5 °
Oscillation	+/- 13 °
Turning radius outside	5200 mm
Gradeability	50 %



Transmission

Final Drive	Torque converter 4 speed power-shuttle transmission, permanent 4 wheel drive, electr. driving direction switch
Steering	hydrostatic center-pivot steering (load Sensing)
Tyres	405/70-20 14 Ply Traction profile
Working brake	foot brake via oil discs in front/rear axle
Parking brake	parking brake via dry disc, acting on gearbox



Hydraulic System

Working pump	gear pump
- flowrate	55 l/min
- oper. press.	220 bar



Tank capacity

Diesel	70 l
Hydraulic	70 l



Electric

Voltage	12 V
Battery	105 Ah
Alternator	40 A
Starter	2,8 kw




Noise Emission

Noise Level LWA (acc. 2000/14/EC)	105 dB(A)
Noise Level LPA (acc. 2000/14/EC)	85 dB(A)



Dimension



	B	B1	C	D	E	F	
mm	2260	2250	470	1050	1900	3620	
	H	H1	K	L	L1	L2	L3
mm	3100	2340	415	4835	2485	1210	1140



Features

- Power swivel skip enabling discharge either side
- Excellent rough terrain performance from hydrost. permanent 4-wheel drive
- Heavy duty construction; skip with 5-8 mm steel plate, reinforced with box sections
- Simple and safe operation; drive direction and speed switch on the steering column.
- Acceleration by foot pedal and braking from hydrost. retardation
- Wide, heavy duty center console protects driver legs
- Simple and clear dashboard including fuel gauge, hourmeter, warning lights for-parking brake, oil filter, oil pressure, engine temperature
- Folding ROPS as standard
- Easy access for service maintenance
- Towing bracket as standard
- Automatic differential lock in front axle



Optional equipment

- Road Lights
- Flashing Beacon
- Reversing Alarm
- Spare Wheel
- Biodegradable hydraulic oil
- Trailer socket
- FOPS roof

Neuson Baumaschinen GmbH
 Haidfeldstraße 37
 A-4060 Linz-Leonding
 Tel. +43 (0) 732/ 90 590-0
 Fax +43 (0) 732/ 90 590-200
 e-mail: verkauf@neuson.com
 www.neusonkramer.com

Lifton Dumpers Ltd
 Crown Business Park,
 Duketown, Tredegar,
 Gwent, NP22 4EF
 United Kingdom

Tel +44 1495 723083
 Fax +44 1495 713941
 e-mail: sales@liftondumpers.com
 www.neusonkramer.com

Kramer-Werke GmbH
 Postfach 10 15 63
 D-88645 Überlingen/Bodensee
 Tel. +49 (0) 7551/ 802-440
 Fax +49 (0) 7551/802-260
 e-mail: info@kramer.de
 www.neusonkramer.com



We reserve the right to change the above specification w/o prior notice.
 044076 - November 2004 - Art.-Nr.: 1000142265



neuson®