

DT22 Scarifier

The DT22 is a truly robust dethatcher, designed for tough, professional jobs under extended periods. Compact design, powerful engine and the unique option of using it as a sowing machine make the DT22 virtually indispensible for lawn care companies etc. Can be fitted with three different types of cutting equipment, and with a collector as well. Ideal for contractors, rental companies and other professional applications.





Compact design

Compact design, low weight and folding handle for easy transport.



Honda GX-engine

High-spec Honda engine. Powerful and easy to start.



Seed hopper

Seed hopper for 14 kg of grass seeds. (accessory). Adjustment for torrent of seed convenient placed on the handle.



Grass collector

230 litre grass collector (accessory).



Commercial components

High-specification components ensure years of reliable use.



Adjustable working depth

Central adjustment for working depth, where depth is adjusted depending on blade wear.

Robust design for demanding,

Technical data

Engine

Engine manufacturer Engine type Power Cylinder displacement Engine lubrication Cooling Air filter Oil type Oil capacity Fuel, minimum Fuel tank capacity Spark plug

Honda **GX 160 OHV** 5.5 hp / 4 kW 7.3 cu.inch / 163 cm³ permanently lubricated air **SAE 10W-30 SF-SG** 0.15 gallon / 0.6l min 86 octane 2.51 / 0.66 gallon NKG BPR6ES

Advantages

Robust design

professional use.

Long life bearings

Sealed, permanently lubricated and selfadjusting bearings provide reliability and long life.

Belt drive

Belt drive with release handle for the

Grow optimising neoprene flap Neoprene flap at the rear of the

machine evens out the soil to optimise growing conditions.

Flail blade reel

Free-swinging flail blades efficiently remove matted thatch/moss with centrifugal force. This design ensures excellent thatch removal and has been proven for more than four decades in the demanding rental equipment business. (accessory)

 Delta blade reel The austempered steel Delta blades have a unique angled position and beveled cutting edges that cut slits in

Transmission

Transmission manufacturer Gear reduction Chassis construction Tyre size, front/rear

Honda 1:6 steel 8x1.75" / 10x1.75"

Equipment

Handle Folding, Foam
Working width 22" / 56 mm
Working depth 25.5 mm
Height adjustment ves

Height adjustment ves
Ball beared wheels ves
Seeder Option
Collector Option

Ergonomics

Overall dimensions

Weight 63 kg

the ground for scarifying, overseeding or aerating . (accessory)

Spring tine reel

Suspension-mounted spring tines remove thatch/moss from well-manicured lawns. In addition, individual spring tines can be quickly replaced without removing the reel assembly. (accessories)